



# Geberit Sigma concealed cistern 8 cm, 6 / 3 litres







# **Application purposes**

- · For masonry walls
- For installation in part- or room-height prewall installations
- · For installation in room-height installation walls
- · For floor-standing WCs
- · For single flush, dual flush or stop-and-go flush

## **Characteristics**

- Series 2016
- Concealed cistern with front actuation
- Concealed cistern fully insulated against condensation
- · Pre-mounted direct plastering netting
- Immediate post flush possible with factory setting
- · Flush bend fitted
- Flush bend adjustable 2 cm upwards and 1 cm downwards
- Tool-free installation and maintenance work on concealed cistern
- · Water supply connection on the top, offset to left side
- · Protection box for service opening can be cut to length, suitable for surface-even actuator plates

## **Technical data**

| Flow pressure                        | 0.1–10 bar    |
|--------------------------------------|---------------|
| Flush volume, factory setting        | 6 and 3 l     |
| Flush volume large, adjustment range | 4.5 / 6 / 7.5 |
| Flush volume small, adjustment range | 3–4           |

## Scope of delivery

- Water supply connection R 1/2", compatible with MeplaFix, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Flush bend with recess shells
- Flush bend extension, ø 45 mm
- · Protection plug
- 2 slotted flat irons
- · Fastening material

# Article

#### Art. no.

## 109.791.00.1

Actuator plate has to be ordered separately