




## Geberit Duofix element for wall-hung WC, 114 cm, with Sigma concealed cistern 8 cm



### Application purposes

- For drywall construction
- For installation in part- or room-height prewall installations
- For installation in room-height installation walls
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- Suitable for wall-hung WCs with projection up to 70 cm
- For single flush, dual flush or stop-and-go flush
- For floor constructions 0–20 cm

### Characteristics

- Series 2016
- Self-supporting frame, powder-coated
- Frame with  $\varnothing$  9 mm drilling holes for fastening in wood frame construction
- Frame suitable for ceramic WC appliances with small contact surface (with pressure-resistant wall covering)
- Galvanized feet
- Leg supports infinitely variable in height
- Non-slip leg supports
- Foot plate depth suitable for installation in U-profiles UW 50 and Geberit Duofix system rails
- Connection bend can be installed without tools at different depths
- Connection bend can be mounted vertically with front flush
- Waste connector bend, extended, for connection in floor
- Fastening for connection bend, sound-absorbing
- Concealed cistern with front actuation
- Concealed cistern fully insulated against condensation
- Immediate post flush possible with factory setting
- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the top, offset to left side
- Protection box for service opening can be cut to length, suitable for surface-even actuator plates
- Equipped with conduit pipe for feed pipe for connection of Geberit AquaClean shower toilets
- With fastening option for electrical connection

### Technical data

|                                      |                 |
|--------------------------------------|-----------------|
| Flow pressure                        | 0.1–10 bar      |
| Flush volume, factory setting        | 6 and 3 l       |
| Flush volume large, adjustment range | 4.5 / 6 / 7.5 l |
| Flush volume small, adjustment range | 3–4 l           |


## Scope of delivery

- Water supply connection R 1/2", compatible with MeplaFix, with integrated angle stop valve and hand wheel
- Protection box for service opening
- 2 wall anchorings
- Connection set for WC, Ø 90 mm
- Connection bend 90° made of PE-HD, Ø 90 mm
- Adapter socket made of PE-HD, Ø 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- Fastening material

## Article

**Art. no.**

**111.796.00.1**

 Actuator plate has to be ordered separately